



Bulk Feed Bin

196 1/2 E 6th St.
PO Box 1265
Sioux Falls, SD 57101

877-782-3073
www.siouxsteel.com



LIVESTOCK



Features

- 4" wide corrugation reduces resistance to downward flow
- 25% more vertical strength than narrow corrugation & twice with no corrugation.
- Increased capacity.
- Reinforced ribs on weather-tight-die-formed roof.
- 23 1/2" diameter, warp-resistant spun cap locks down tight to keep moisture out.
- Bin sheets made of G-90 galvanized steel.

Options: Wide variety of bottom attachments.
Boots for automated feed delivery systems or rigid augers and slide gates.



Specifications - 60°/67° Hopper opening - 40# cu. ft. capacity

MODEL	FULL HEIGHT	TON	BUSHEL	CUBIC FEET	
6X1	10'8"	2.7	108	134	6' diameter bin w/60° hopper & 30" ground clearance
6X2	13'4"	4.3	168	209	
6X3	16'0"	5.9	228	284	
6X4	18'8"	7.5	288	359	
7X1	13'9"	4.6	184.8	230	7' diameter bin w/67° hopper & 27" ground clearance
7X2	16'5"	6.7	269.2	335	
7X3	19'1"	8.9	357.6	445	
7X4	21'9"	11.1	446	555	
7X5	24'5"	13.3	534.4	665	
7X6	27'1"	15.4	618.7	770	
9X1	14'2"	7.4	294	366	9' diameter bin w/60° hopper & 26" ground clearance
9X2	16'10"	11	431	536	
9X3	19'6"	14.6	567	706	
9X4	22'2"	18.2	704	876	
9X5	24'10"	21.8	840	1046	
9X6	27'6"	25.4	977	1216	